Cleaner CDK Code #3: run the PMD tests

Egon Willighagen

Published March 26, 2010

Citation
Willighagen, E. (n.d.). In *chem-bla-ics*. chem-bla-ics. https://doi.org/10.59350/0jvd2-er861

Keywords
Cdk, Pmd

Copyright
Copyright © Egon Willighagen 2010. Distributed under the terms of the Creative Commons Attribution 4.0 International License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

PMD is a tool to run some tests against your source code. The check for code style, common problems, and places where code could be improved. The CDK has been using it for years now, such as here for CDK 1.3.x.

Running the PMD tests from the command line

When you are writing patches for the CDK, you can run the PMD tests via an Ant file, for example via the command line:

```
$ ant -f pmd.xml
```

However, when working on a single file, you will likely appreciated running the tests against a single module. This can be done with (for the data module):

```
$ ant -f pmd.xml -Dpmd.test=custom -Dmodule=data test-module
```

The custom.xml defines the tests we normally run.

The pmd.xml does not create HTML pages, like Nightly does. Instead, an XML file is currently created. The xpath utility can be used to filter out the information we are interested in. For example, if we want to reports just about DefaultChemObjectBuilder, we issue:

```
$ xpath -e "//violation[@class='DefaultChemObjectBuilder']" \\
    reports/pmd/data.xml
```